

CONNECTIVITY SOLUTIONS START HERE

Browse Newark's huge range of industrial connectivity solutions – ready to ship today!

FREE 2-4 Day Delivery
on orders over \$150.

Flat rate shipping of \$9.99
for orders under \$150*

* Some exclusions apply

See at newark.com/help-delivery-information



Find more online at

newark.com

1.800.463.9275



Table of contents

4	PCB connectors	22	Switches & sensors
5	Circular connectors	23	Relays & ethernet switches
6	Cable assemblies & terminal blocks	24-25	Tools & production supplies
7	IO connectors	26-27	Bench test instruments
9	Terminals, tooling & RF connectors	28	Field instrumentation
10	RF connectors	29	Test connectors & cable assemblies
11	Interconnect & wire	30	Multicomp Pro connectors & more
13	XLR connectors & production supplies	31	Multicomp Pro test equipment & more
14-15	Wire & cable	32	Passive components
17-18	Cable management	34	Semis & optoelectronics
20	Enclosures, fans & more		

Find thousands of in-stock connectors, wire, cable, components & test equipment in stock at newark.com

How may we help you today?

Website
newark.com

Email
order@newark.com
quote@newark.com

Phone
1.800.463.9275
M-F 7:00 AM – 8:00 PM (EST)

Fax
1.888.551.4801

eProcurement systems
We can link with any eProcurement system and our dedicated e-team will facilitate your implementation.
email: eproc@newark.com

Same-day shipping
newark.com/shipping
Domestic: Order M-F by 9:30 PM (EST)
Export: Order M-F by 6:00 PM (EST)
In-stock products normally ship the same day

No minimum order fees



You can find us at...



An Avnet Company © 2020 Premier Farnell Limited. All rights reserved. Newark is a trading name of Premier Farnell Limited. This information is of a general nature and is not intended to address the circumstances of any particular individual or entity. No one should act on such information without appropriate professional advice. Please see our website, newark.com, for updated information. The information and pricing contained on our website supersedes the information contained in any printed catalog or other publication. Printed in the U.S.A. WF- 2579611

3M™ Mini-Clamp, Link and Power Clamp Connectors

Time-saving, reliable and field-installable
wiring solutions



PCB CONNECTORS

Receptacles Make KeySwitch Hot Swapping Effortless

Mill-Max receptacles enable efficient replacement or upgrade of keyboard switches and other PCB components.



Mill-Max

Micro HDAS board to board and board to wire connectors

Micro HDAS allows you to save space on your board while maintaining a high level of performance. Offering you PC Tail & crimp contact terminations, Micro HDAS provides a modularity to fit all your needs.

Amphenol
Aerospace



Econoseal Connector Series

Offers full market portfolio for wire-to-wire, wire-to-board, and wire-to-device applications




TE

Search
[39AJ5738 at newark.com](#)

MTMM Series 2.00 mm Variable Post Height Terminal Strips

Industry's largest variety of low profile pin counts, terminal lengths and options up to four rows and 200 total pins.



samtec

Search
[83AH7401 at newark.com](#)

1.0mm centerline locking High Performance Interconnect (HPI) solution

TE's new 1.0mm centerline locking High Performance Interconnect (HPI) solution addresses the needs of low-profile applications that require a reliable, secure wire-to-board signal or low-power connection.



TE

Search
[92B1055 at newark.com](#)

Easy-On FFC/FPC connectors

Easy-On FFC/FPC connectors deliver a versatility unmatched by others with terminal pitches that range from 0.20mm to 2.00mm for applications from tiny wireless earbuds to automotive.



molex

Search
[20W4379 at newark.com](#)

KK Series Interconnect Solutions

KK connector systems are customizable for a variety of power and signal applications.



molex

Search
[78AH6784 at newark.com](#)

Micro-Fit+ Connectors

The Micro-Fit+ connector is a wire-to-board system which offers a 3.00mm pitch, a higher-current rating of 12.5A and superior design options for flexibility and efficient assembly



molex

Search
[13AJ2308 at newark.com](#)

Gecko-MT 1.25mm pitch Mixed Layout Connectors

The new Gecko-MT range combines the 1.25mm pitch Gecko signal connector system with mixed technology layouts, adding 10A power contacts to the range. The smallest and lightest mixed-layout connector available.



HARWIN

Search
[26H0648 at newark.com](#)

16G 0.5mm free height stacking connectors

TE's stacking connector portfolio includes free height, fine stack and fine mate connectors. These products provide various flexible stacking solutions for mezzanine (vertical, parallel stacking board-to-board) connections.



TE

Search
[83AH0172 at newark.com](#)

BergStak® 0.40mm Self-Alignment Board-to-Board Connectors

The BergStak® 0.40mm self-alignment connectors come with a stack height of 3.50mm and 30 positions extendable up to 10 to 60 positions with 10 positions incremental.



Amphenol
ICC

Search
[83AH1887 at newark.com](#)

CIN::APSE® Compression Technology

CIN::APSE® is a unique, Z-Axis compression interconnect which provides superior mechanical and electrical performance. The contact construction consists of randomly wound gold plated molybdenum wire, formed into a cylindrical shape



cinch
COMMUNITY SOLUTIONS
TECHNOLOGY

Search
[36AJ6766 at newark.com](#)

8142 Z series PCB Connector

Designed for applications where the wire connection needs to be installed in one half of the housing and the printed circuit board with the pin-strip header is installed in the housing that snaps into the base plate.



wieland

Search
[83AH7491 at newark.com](#)

Minitek® MicroSpeed 1.00mm Board-to-Board Connectors

Minitek® MicroSpeed connector family with 1.00mm pitch supports high-speed data applications with up to 25Gb/s.



Amphenol
ICC

Search
[84AC6155 at newark.com](#)

Flexible Ultra Micro Power System

Micro 2.00 mm Pitch High-Power Interconnects



samtec

Search
[45X9595 at newark.com](#)

Search
[80AH9100 at newark.com](#)

Search
[95AC5501 at newark.com](#)

ODU MEDI-SNAP® – Circular Plastic Connector with Push-Pull & Break-Away Locking

Combines distinctive keying options with over 2,000 mating cycles. This connector is available both with user-friendly Push-Pull locking and easy to release Break-Away function which comes as a premolded plug & play solution.



Hermetic Circular Connectors

Amphenol Aerospace's hermetic circular connector line offers superior electrical performance plus the rugged design of a glass-sealed connector with superior leak rate performance



Amphenol-Lite M3 High performance Circular Connectors

Based on the MIL-DTL-38999 III and designed for harsh environments



Search
[33AH3475 at newark.com](#)

97 Series Connectors with Gray ZnNi plating

Gray Zinc/Nickel plating provides an ideal RoHS compliant solution for harsh, high corrosive environments



Search
[08AJ1954 at newark.com](#)

The Intercontec 923 series Circular Connectors

With options of 6, 8, 9 and 10 poles it offers classic power supply but even possibilities for hybrid applications like communicating hyperface protocols



Search
[52AC2000 at newark.com](#)

MIL-DTL-38999 Circular Connectors

With three coupling methods, nine shell sizes, and a wide variety of contact arrangements, the connectors help give you the range of choices you need.



Search
[54AC6862 at newark.com](#)

Swing-Arm® strain relief backshells

The Glenair articulating three-in-one Swing-Arm® strain relief backshell is an innovative cable clamp with EMI / RFI cable shield termination options for a wide range of EWIS applications.



Search
[73AH9745 at newark.com](#)

KPT Series 26482-Style miniature-circular connectors

Environmentally sealed, fully intermateable and accept a wide range of interchangeable accessories



Search
[07X6830 at newark.com](#)

MPRINTO-M12 Push-Pull Connectors

World's First True Backward Compatible To All M12*1.0 Thread Socket Unique Technology Patent



Search
[29AJ3671 at newark.com](#)

DMS-TP Series Dry-mated Sealed Connectors

Meet the highest largest of safety for the harsh environment applications. Very effective in harsh environment applications with prolonged use in the presence of oil, gas, sand, mud, hydrocarbons, and salt.



Search
[98F9654 at newark.com](#)

M5 Sensor Connectors

The most compact connector type in the M-Series range, our waterproof M5 sensor connectors come in straight and angled forms with PVC or PUR overmolded cable connector options and a variety of panel mount receptacles.



Search
[86AH2044 at newark.com](#)

KV Series Circular Connectors

Circular connectors with threaded joint M16 acc. to IEC 61076-2-106, IP40/IP68



Search
[82AH4113 at newark.com](#)

ecomate® RSSM (Rugged Superior Seal Metal) Series circular connectors

The ecomate® RSSM (Rugged Superior Seal Metal) Series of circular, metal connectors provides an IP69K rating (in mated condition) for industrial applications all in a silicone sealed connector system.



Search
[37AC2344 at newark.com](#)

MIL-DTL-38999 Series III Connectors

MIL-DTL-38999 Series III connectors are available in wide range of shell materials and finishes with 48, 500, 1000 and 2000 hour salt spray plating exposure.



Search
[82AH3330 at newark.com](#)

MIL-DTL-26482 Series II Connectors

High reliability, moisture, corrosion and fluid resistant. Shell to shell conductivity and superior contact stability.



Search
[02AH3525 at newark.com](#)

Search
[96J2512 at newark.com](#)

Search
[80P6467 at newark.com](#)

CABLE ASSEMBLIES & TERMINAL BLOCKS

Lighted M12 Cordsets

A wide variety of lighted M12 cordsets that provide bright indication of sensor power and output status.



PCB 1,000 Volt Insulated Terminal Blocks

OT-017F-M4 1,000V / 60A OP-930-P35 1,000V / 40A UL/CSA/ RoHS



Mini-Con-X Insta-Click Harsh Environment Connectors

This cost effective connector is sealed to IP68, has an automatic positive lock, and is made in USA to withstand any harsh environment application.



Search
[49AJ2936 at newark.com](#)

Nano-Fit Off-the-Shelf (OTS) Overmolded Cable Assemblies

Nano-Fit Double-Ended, Overmolded Cable Assemblies with strain relief offer off-the-shelf and customized versions with various circuit sizes and lengths.



Search
[21AJ9737 at newark.com](#)

Off-the-Shelf (OTS) Mega-Fit Overmolded Cable Assemblies

Molex delivers off-the-shelf and customized Mega-Fit Overmolded Cable Assemblies in multiple circuit sizes and lengths, combining rugged signal connection with a user friendly interface.



Search
[73AH8468 at newark.com](#)

OptoUSB USB 3.1 AOC Assemblies

OptoUSB USB 3.1 Active Optical Cable Assemblies offer familiar passive plug-and-play interfaces with reliable signal integrity performance up to 100.0m, and they deliver uncompressed video with superior resolution.



Search
[58AC8104 at newark.com](#)

Single Pair Ethernet - The enabler for industry 4.0 and the IIoT

T1 connectivity makes Ethernet easy and affordable - and it can be used from the cloud to the smallest sensor



Search
[58AC8093 at newark.com](#)

M12 X-Code Cable Assemblies

Available in both M12 X-Code Male to M12 X-Code Male and M12 X-Code Male to an over molded RJ45 male plug.



Search
[23AH8958 at newark.com](#)

Entrelec SNK Series Terminal Blocks and Accessories

The innovative SNK series is available in PI Spring (Push-In and Spring), screw clamp and pluggable technologies with common accessories. Qualified for worldwide applications and severe environments.



Search
[67AH8690 at newark.com](#)

Eaton's XB Series - DIN Rail Mount Terminal Blocks

Compact Design Terminal Block with single feed screw connections.



Search
[83AH0026 at newark.com](#)

Maximum flexibility in PCB design

With the push-in technique for wire insertion, this very compact, single pole terminal block features a high level of connection reliability with its wire connection indicator and test point for a continuity check



Search
[99AC3237 at newark.com](#)

DBL Power Distribution Blocks

The exclusive compact and modular design of our power distribution blocks allows easy installation combined with a great flexibility of use.



Search
[47T6251 at newark.com](#)

2600 Series PCB Terminal Blocks

Feature Push-In CAGE CLAMP® connection technology allow for increased pin spacing and double pinning to allow for expanded current capacities while maximizing voltage ratings.



Search
[37AC4515 at newark.com](#)

Omnimate 4.0 Pluggable Terminal Blocks

OMNIMATE® 4.0 is the efficient solution for a continuous, digitalized device development process for the connected world of tomorrow.



Search
[72AC3584 at newark.com](#)

134 Series Power Distribution Blocks

Provides panel builders an open style listed Power Distribution Block that complies to the latest feeder circuit requirements for amp ranges 175-510A.



Search
[74AH2827 at newark.com](#)

Search
[23AJ4874 at newark.com](#)

Search
[78AC5559 at newark.com](#)

AC Receptacles



A complete range of AC receptacles including NEMA outlets, IEC Inlets and Outlets, multi-function modules, and Filtered multifunction modules. Designed and approved to most international safety agency requirements.

Search
[17B6838 at newark.com](#)

50/50 Split Passive Optical Tap



The TAP-LCM4-5050-LGX is designed for use with OM4 Multimode Fiber and features LC/UPC connectors.

Search
[04AJ6338 at newark.com](#)

D-Subminiature Backshells, Contacts & Accessories



Standard, High-Density, Combo-D, IP67 Waterproof, Stacked and hermetic connectors available

Search
[67AH5576 at newark.com](#)

NANOOK IP67 D-Sub Connectors



NANOOK flanged waterproof d-sub connectors offer an all-inclusive solution for a wide range of applications, including: telecommunication equipment, computer technology, and harsh environment applications.

Search
[76AH5184 at newark.com](#)

CTC Series environmentally sealed cable-to-cable interconnects



A high performance, cost effective, cable-to cable solution for use in harsh environment applications where reliable signal circuits are critical to operating performance.

Search
[48AC9073 at newark.com](#)

Micro-D Connectors M83513



The Amphenol Micro-D connector series (M83513) offers proven military spec performance and reliability in rectangular and stripline micro connectors

Search
[12AJ6342 at newark.com](#)

Fiber Coupler, LC/LC Duplex Ceramic Sleeve, No Flange



Duplex plastic LC couplers are designed for mounting in panels with rectangular cutouts. These adapters feature ceramic alignment sleeves which provide precision mating for both Multimode and Single Mode applications

Search
[89M9628 at newark.com](#)

USB 2.0 Type-C Connectors



New 16 Circuit USB 2.0 Type-C Connectors are suitable for compact, waterproof and fast charging applications

Search
[13AJ2447 at newark.com](#)

END Series Sealed RJ45 Connectors



The new END series from offers reliable, harsh environment performance in a small package. Incorporating an RJ45 connector into a sealed housing ensures the connectors are easy to terminate, offering data performance up to CAT6.

Search
[84AH3969 at newark.com](#)

Amphenol Sine Systems' BoardLock™ Family



Combines flanged or flangeless, 180° straight or 90° right angle pin-oriented, wire-to-board versatility with the proven reliability of the A Series™ environmentally-sealed thermoplastic connection.

Search
[40AH1800 at newark.com](#)

MPO Fiber Optic Connector



L-com's IP68 series MPO is 24-fiber, low-loss Multimode without guide pins (female) connector. The 4.8mm crimp option supports 4.5mm to 4.9mm fiber diameters

Search
[83AH9595 at newark.com](#)

DL Series Zero Insertion Force (ZIF) Connectors



Engineered to operate in a variety of medical, industrial, test and measurements applications, these connectors fill the need for cost-effective, multiple-wire power and signal interconnect solutions.

Search
[51R5891 at newark.com](#)

HiPer-D® (M24308 Style) Connectors

Watch Video



The Glenair Series 28 HiPer-D® connector is intermateable and intermountable with large M24308 type D-Subs, but meets the need for improved performance in rugged environments.

Search
[29AJ3653 at newark.com](#)

USB4125 USB Type C format connector



GCT's ionex® USB4125 is a breakthrough USB type C connector for charging applications.


Search
[08AJ1663 at newark.com](#)

Ethernet Jacks with integrated magnetics and PoE



Offer a highly integrated connectivity PCB solution for Industrial Ethernet applications.

Search
[99AC2240 at newark.com](#)



YOUR WRISTS WILL THANK US

NO-TWIST COMPACT SPLICING CONNECTORS

- Comfortable, tool-free lever operation
- Test port located on the front and back for convenience
- 2-, 3-, 5-wire versions for all wire types
- 12 AWG family: 24 - 12 AWG; 20 A / 600 V
- 10 AWG family: 20 - 10 AWG; 30 A / 600 V



2D Amplivar Terminals SPLICE

TE Connectivity's 2D Crimp Amplivar Splices are a magnet wire splice solution that allows the use of one splice and a single adjustable applicator across many different wire sizes (600CMA to 7000CMA).



Search
[31AJ9960 at newark.com](#)



Triton Grounding Jumper Solutions

UL-certified off-the-shelf Triton Grounding Jumpers enable the safe management of high-power applications and customized versions offer variable lengths and terminations.



Search
[52AH3553 at newark.com](#)



Battery Compression Lugs

Provide OEM quality termination for Heavy Duty power connector applications. The Panduit BCL products are part of a complete offering of power connectors, lugs and tooling to provide a complete solution.



Search
[51AH4506 at newark.com](#)



Solderless Terminals

A wide range of 3M Terminals & Splices in stock at Newark!



Search
[89T8622 at newark.com](#)

Pre-Insulated POD-LOK Receptacle Terminals

Combine Positive Lock receptacles with Glow Wire Test (GWT), UL 94 V-0 rated housings.



Search
[69AC4677 at newark.com](#)



Panduit CT-2300/ST Battery Powered Crimp Tool

The CT-2300/ST BlackFin® Battery Powered Crimping Tool has interchangeable crimp dies for terminating most Pan-Term® terminals, splices, disconnects, ferrules and some copper lugs.



Connector Tooling

A wide range of Crimp Tools, Insertion & Extraction Tools, Locators in stock



T-Head Hand Crimp Tool

The 59250 is a T-Head Hand Crimp Tool for AMP PIDG/STRATO-THERM/PLASTI 26-14AWG terminals and splices.



Search
[50F546 at newark.com](#)



CERTICRIMP 2 Premium Crimp Tool

CERTI-CRIMP hand tools are top-of-the-line, premium hand-operated tools for crimping a broad array of terminals, contacts and special wiring devices.



Search
[90B3914 at newark.com](#)

PremiumGrade Hand Crimp Tool

Features a full cycle ratcheting hand tool ensures complete crimps and a precision user-friendly terminal locator wire stop holds terminals in the proper crimping position



Light Duty Side Feed Terminal Cutter

Designed to cut side-feed, front-carrier terminals from the carrier strip



Search
[56AC1977 at newark.com](#)



Tetra Hand Crimp Tool

Designed to crimp the terminals and splices onto stranded wire sizes 22 through 10AWG. Each hand tool features two crimping dies, a spring-loaded locator assembly and a ratchet handle with a ratchet pawl.



Search
[35M4806 at newark.com](#)

12G HD-BNC straight plug to BNC straight plug on Belden 4855R

Amphenol RF offers a full line of fixed length cable assemblies optimized for 12G SDI 4K and Ultra-HD broadcast applications.



Keyspan USB to Serial Adapter

The Keyspan USA-19HS USB to serial adapter connects devices with a 9-pin serial port, such as switches, routers, barcode scanners and lab equipment, to your computer or laptop USB-A port.



Search
[05R5133 at newark.com](#)



Search
[82F9908 at newark.com](#)

7-Port Industrial-Grade USB 2.0 Hub

Rugged industrial-grade hub adds 7 USB 2.0 ports to your computer for connecting industrial printers, sensors and other USB devices.



Search
[18AC7016 at newark.com](#)

RF CONNECTORS

RF Terminator- SMA Male



RF Coaxial Right Angle Adapter



RF Fixed Attenuator



L-com's LCTR1001 is an RF termination that operates from DC to 1 GHz and handles up to 2 Watt (CW). This SMA termination/load has a male gender.



The L-com LCADS30034 is a right angle adapter with a female to male configuration. Quality construction uses brass with nickel finish and N interface defined by MIL-STD-348A



The 20 dB Fixed Attenuator LCAT1003-20 is fixed rated to 2 Watts and operates from DC to 3 GHz. The versatile coaxial packages uses type N male to type N female connectors and is also RoHS compliant.



Search
[38AH5070 at newark.com](#)

Search
[83AH8916 at newark.com](#)

Search
[38AH5056 at newark.com](#)

High Density NanoRF Module



NanoRF Connectors for VITA 67.2



TE Connectivity BNC Connectors



NanoRF, PCB RF Module, 18 coaxial contacts, vertical



VITA 67 PCB RF Module, 8 coaxial contacts



COAXICON 50-Ohm RF Series BNC Plug Connectors



Search
[78AH2858 at newark.com](#)

Search
[08X2952 at newark.com](#)

Search
[44F7871 at newark.com](#)

TE Connectivity BNC Connectors



SMA Male to Male 6" Cable Assembly for .047 SuperFlex Cable



SMA Female Bulkhead to SMA Male 6" Cable Assembly for .047 Cable



COAXICON 50-Ohm RF Series BNC Plug Connectors



Fixed length RF cable assemblies using its most flexible 0.047" cable yet! This super flexible coax cable is capable of extreme bends which allow it to fit in tight spaces and route for any application.



Just released large SMA and 2.92mm female bulkhead cable assemblies used to transmit a signal through a panel using a single mounting hole. Allows installation through a box or panel without the use of screws.



Search
[42K7115 at newark.com](#)

Search
[76AH8150 at newark.com](#)

Search
[17AJ3721 at newark.com](#)

SV's new SMA Edge-Lock PCB connector allows for precision placement prior to reflow



N Type Jack to SMA Jack Straight Bulkhead Adapter



IP67 BNC Straight Plug for RG-316



Developed to form an interference fit between the conical alignment pin and the PCB thru-hole, thus pulling the contact lane of the connector in to the edge of the PCB. The result is a fixture-less connector.



50 ohm RF between-series coaxial adapter commonly used in applications requiring two dissimilar RF interfaces to be connected.



A sealed waterproof solution 50 ohm RF connector featuring popular bayonet coupling mechanism for secure and easy mating.



Search
[26AJ4731 at newark.com](#)

Search
[92C7273 at newark.com](#)

Search
[22AJ1933 at newark.com](#)

Edge mount SMA Jack



PCB edge mount SMA jack



RF Adapter



Edge mount straight SMA jack connector. Rated at 50 ohms.



The BU-1420701801 is a low-loss, PCB edge mount SMA jack with a round contact. Intended to be mounted on 0.062" (1.57mm) circuit boards.



The BU-P72973 is a female to female SMA flange mount connector rated at 50 ohms



Search
[52AH3438 at newark.com](#)

Search
[52AH3434 at newark.com](#)

Search
[17AH8714 at newark.com](#)

Keyspan USB to Serial Adapter

The Keyspan USA-19HS USB to serial adapter connects devices with a 9-pin serial port, such as switches, routers, barcode scanners and lab equipment, to your computer or laptop USB-A port.



7-Port Industrial-Grade USB 2.0 Hub

Rugged industrial-grade hub adds 7 USB 2.0 ports to your computer for connecting industrial printers, sensors and other USB devices.



Ultra High Speed HDMI Cable VHA00021-0.5M 19.7"

L-com VHA00021 line of Ultra High Speed 8K HDMI cables are the latest and greatest in HDMI technology. Meeting HDMI 2.1 specifications, the half meter VHA00021 line is capable of handling resolutions of 8k@60Hz.



Search
[05R5133 at newark.com](#)

Ultra High Speed HDMI Cable VHA00021-1M 3.3ft

L-com VHA00021 line of Ultra High Speed 8K HDMI cables are the latest and greatest in HDMI technology. Meeting HDMI 2.1 specifications, the half meter VHA00021 line is capable of handling resolutions of 8k@60Hz.



Search
[68X4612 at newark.com](#)

Ultra High Speed HDMI Cable VHA00021-2M 6.6ft

L-com VHA00021 line of Ultra High Speed 8K HDMI cables are the latest and greatest in HDMI technology. Meeting HDMI 2.1 specifications, the half meter VHA00021 line is capable of handling resolutions of 8k@60Hz.



Search
[43AJ7036 at newark.com](#)

Ultra High Speed HDMI Cable VHA00021-3M 9.8ft

L-com VHA00021 line of Ultra High Speed 8K HDMI cables are the latest and greatest in HDMI technology. Meeting HDMI 2.1 specifications, the half meter VHA00021 line is capable of handling resolutions of 8k@60Hz.



Search
[43AJ7037 at newark.com](#)

Thinline High Speed HDMI Cable with Ethernet VHA00022-1F 1ft

ThinLine cable diameter for tight spaces. Gold contacts to minimize signal loss.



Search
[43AJ7038 at newark.com](#)

Thinline High Speed HDMI Cable with Ethernet VHA00022-10F 10ft

ThinLine cable diameter for tight spaces. Gold contacts to minimize signal loss.



Search
[43AJ7039 at newark.com](#)

Thinline High Speed HDMI Cable with Ethernet VHA00022-3F 3ft

ThinLine cable diameter for tight spaces. Gold contacts to minimize signal loss.



Search
[43AJ7040 at newark.com](#)

Thinline High Speed HDMI Cable with Ethernet VHA00022-6F 6ft

ThinLine cable diameter for tight spaces. Gold contacts to minimize signal loss.



Search
[43AJ7041 at newark.com](#)

Mini Displayport to HDMI Cable Assembly VPA00005-1M 3.3ft

Mini DisplayPort interfaces commonly used on small form factor devices and mobile devices



Search
[43AJ7042 at newark.com](#)

Mini Displayport to HDMI Cable Assembly VPA00005-3M 9.8ft

Mini DisplayPort interfaces commonly used on small form factor devices and mobile devices



Search
[43AJ7043 at newark.com](#)

U100 Series Unbalanced Cable, 100ft

This cable can handle the rigors of any audio environment. The PE insulation ensures the best possible signal flow and extends the useful life of the cable



Search
[43AJ7047 at newark.com](#)

U100 Series Unbalanced Cable, 500ft

The improved conductivity of the U100 Series bare copper conductors ensure that your signal will be strongest when it reaches the destination



Search
[43AJ7048 at newark.com](#)

Cable, Balanced, Patch, Bulk, 500ft

The B1000 Series balanced cable is made using two stranded, 26AWG, oxygen-free bare copper conductors in a tight-pitch twisted pair configuration.




Search
[43AJ7056 at newark.com](#)

Search
[43AJ7057 at newark.com](#)

Search
[43AJ7058 at newark.com](#)

SELOS[®], FASIS[®], WIECON[®], SAMOS[®]

HIGHLY **RELIABLE.**
SAFE.



BROWSE PRODUCTS

www.newark.com/b/wieland-electric

B Series XLR Chassis Connectors



IO Audio B Series XLR Connector IO-XLR3-F-BH is a Locking Horizontal PCB Mount 3 contact Female chassis connector for Audio and Lighting control



Search
[92AH3641 at newark.com](#)

B Series XLR Chassis Connectors



IO Audio B Series XLR Connector IO-XLR3-M-BV is a Locking Vertical PCB Mount 3 contact Male chassis connector for Audio and Lighting control



Search
[92AH3654 at newark.com](#)

B Series XLR Chassis Connectors



IO Audio B Series XLR Connector IO-XLR5-M-BH is a Locking Horizontal PCB Mount 5 contact Male chassis connector for Audio and Lighting control



Search
[92AH3686 at newark.com](#)

Electrically Conductive, Silver-filled Two-part Epoxy Adhesive.



Allows for quick, cold-soldering repairs. It can also be used as a solder replacement for bonding heat-sensitive electronic components, or for making conductive connections where soldering is not an option.



Search
[20X4797 at newark.com](#)

Tweezer, Precision, Curve, Pointed, Stainless Steel, 4.5 "

The 7SASL is a 4.5-inch precision point Tweezer with stainless steel body and tip construction. Anti-magnetic and Curved for easy manipulation in confined areas



Search
[52F9070 at newark.com](#)

B Series XLR Chassis Connectors



IO Audio B Series XLR Connector IO-XLR3-F-BV is a Locking Vertical PCB Mount 3 contact Female chassis connector for Audio and Lighting control



Search
[92AH3645 at newark.com](#)

B Series XLR Chassis Connectors



IO Audio B Series XLR Connector IO-XLR5-F-BH is a Locking Horizontal PCB Mount 5 contact Female chassis connector for Audio and Lighting control



Search
[92AH3677 at newark.com](#)

B Series XLR Chassis Connectors



IO Audio B Series XLR Connector IO-XLR5-M-BV is a Locking Vertical PCB Mount 5 contact Male chassis connector for Audio and Lighting control



Search
[92AH3690 at newark.com](#)

Potting Compound, 2 Part Epoxy, 375 ml



832B potting and encapsulating compound is a black, general purpose, hard, two-part epoxy that offers extreme environmental, mechanical and physical protection for printed circuit boards and electronic assemblies.



Search
[20X1119 at newark.com](#)

Standoff, Ceramic, 6-32, Round Female, 12.7 mm, 12.7 mm

Ceramic Standoff Ideal for very high temperature conditions, Exceptional strength in compression and tension and Withstands very high voltage without flashback



Search
[94F4393 at newark.com](#)

B Series XLR Chassis Connectors



IO Audio B Series XLR Connector IO-XLR3-M-BH is a Locking Horizontal PCB Mount 3 contact Male chassis connector for Audio and Lighting control



Search
[92AH3650 at newark.com](#)

B Series XLR Chassis Connectors




IO Audio B Series XLR Connector IO-XLR5-F-BV is a Locking Vertical PCB Mount 5 contact Female chassis connector for Audio and Lighting control



Search
[92AH3681 at newark.com](#)

Removal Kit for SMD Components



Chip Quik Alloy for SMD Removal, 2.5ft, flux, alcohol pads. Leaded.



Search
[07C9609 at newark.com](#)

Tweezer, ESD, Straight, Round, Stainless Steel, 125 mm Overall Length

Static Dissipative Special alloyed, Non-Rusting, Stainless Steel Coated by ESD-Safe Dissipative Material Anti Magnetic and Acid resistant For all current Electronics Applications



Search
[28C1851 at newark.com](#)

Anti Static Wrist Strap Tester, with 10mm Snap Socket & 2x Banana Plug Sockets

An ESD Wrist Strap Tester with 10mm nickel-plated snap socket (rear) and 2 nickel-plated banana plug sockets for wrist strap cord attachments. Simply touch the unit and a green light & audible sound indicate proper ground.



Search
[02B1658 at newark.com](#)

Alpha Wire Xtra-Guard Flex TPE Cable

This 14AWG, 5 conductor 1000ft TPE Cable combines physical toughness and continuous flex performance in one cable



Alpha Wire Xtra-Guard Flex TPE Cable

This 18AWG, 7 conductor 100ft TPE Cable combines physical toughness and continuous flex performance in one cable



Alpha Wire Xtra-Guard Flex TPE Cable

This 18AWG, 12 conductor 100ft TPE Cable combines physical toughness and continuous flex performance in one cable



Search
[23AJ4940 at newark.com](#)

EcoGen EcoWire Metric

Alpha Wire 67010 BK033 100m MPPE wire is used in metric applications where size, weight, and space matter



Search
[23AJ5239 at newark.com](#)

EcoGen EcoWire Metric

Alpha Wire 67050 BK033 100m MPPE wire is used in metric applications where size, weight, and space matter



Search
[23AJ5243 at newark.com](#)

EcoGen EcoWire Metric

Alpha Wire 67050 OR321 50m MPPE wire is used in metric applications where size, weight, and space matter



Search
[42AH9129 at newark.com](#)

EcoGen EcoWire Metric

Alpha Wire 67075 BK033 100m MPPE wire is used in metric applications where size, weight, and space matter



Search
[42AH9163 at newark.com](#)

Xtra Guard Industrial Ethernet Flex

Alpha Wire TL75031 TL005 24AWG 100ft cable is the perfect solution for Robotics, medical, automation, and transportation applications



Search
[42AH9171 at newark.com](#)

Xtra Guard Industrial Ethernet Flex

Alpha Wire TL76030 TL005 24AWG 100ft cable is the perfect solution for Robotics, medical, automation, and transportation applications



Search
[42AH9179 at newark.com](#)

Xtra Guard Industrial Ethernet Flex

Alpha Wire TL75030 TL001 24AWG 1000ft cable is the perfect solution for Robotics, medical, automation, and transportation application



Search
[78AH8716 at newark.com](#)

Xtra Guard Industrial Ethernet Flex

Alpha Wire TL75030 TL005 24AWG 100ft cable is the perfect solution for Robotics, medical, automation, and transportation applications



Search
[78AH8724 at newark.com](#)

Pro-Met® Industrial VDE Cable

Alpha Wire 470021CY GE033 17AWG 2 conductor 100m cable is used in metric applications where size and weight matter



Search
[78AH8713 at newark.com](#)

Pro-Met® Industrial VDE Cable

Alpha Wire 470021YY GE033 17AWG 2 conductor 100m cable is used in metric applications where size and weight matter



Search
[78AH8714 at newark.com](#)

Pro-Met® Industrial VDE Cable

Alpha Wire 470025CY CL321 21AWG 2 conductor 50m cable is used in metric applications where size and weight matter



Search
[07AH7718 at newark.com](#)

Pro-Met® Industrial VDE Cable

Alpha Wire 470025CY GE033 21AWG 2 conductor 100m cable is used in metric applications where size and weight matter



Search
[07AH7720 at newark.com](#)

Search
[07AH7723 at newark.com](#)

Search
[07AH7724 at newark.com](#)

Belden 10GX24 Cat 6A Enhanced Cable



Belden's 10GX24 is 625MHz, 1000ft, 4 Pair, 23AWG Solid pair copper conductors, LSZH White Jacket designed for multi-gigabit applications



Search
[14R9728 at newark.com](#)

Belden 10GXW Category 6A Copper Cable



Belden's newest cable, 10GXW, is the industry's smallest-diameter Category 6A cable designed for smart building and multi-gigabit applications 10GXW13 0101000 is 1000ft, 23AWG, Black Jacket



Search
[41AH9219 at newark.com](#)

Belden RS-485 Direct Burial Cable 3107DB 0101000



Belden® Classics Cables provide best in class performance for a wide range of applications: Video, Sound, Security, Industrial and Interconnect



Search
[41AH7737 at newark.com](#)

ETHERLINE® TRAY CAT5e



Etherline® 2170299 is a 4 pair Cat5e cable. Designed for flexible networking applications. 500ft, LSZH Jacket, 26AWG, and shielded for EMI protection



Search
[78AH6806 at newark.com](#)

ETHERLINE® TRAY CAT.7



Etherline® 2170472 Cat.7 cable designed for stationary applications with performance and maximum transfer rate (IEEE 802.3). PLTC, Ethernet/IP. 500ft, 22AWG, and shielded (IEC 61156-5)



Search
[78AH6809 at newark.com](#)

Belden 10GXW Category 6A Copper Cable



Belden's newest cable, 10GXW, is the industry's smallest-diameter Category 6A cable designed for smart building and multi-gigabit applications 10GXW13 D151000 is 1000ft, 23AWG, Blue Jacket



Search
[41AH9212 at newark.com](#)

Belden RS-485 Direct Burial Cable 3105DB 0101000



Belden® Classics Cables provide best in class performance for a wide range of applications: Video, Sound, Security, Industrial and Interconnect



Search
[41AH7735 at newark.com](#)

Belden RS-485 Direct Burial Cable 3108DB 0101000



Belden® Classics Cables provide best in class performance for a wide range of applications: Video, Sound, Security, Industrial and Interconnect



Search
[41AH7738 at newark.com](#)

ETHERLINE® TRAY CAT5e



Etherline® 2170299 is a 4 pair Cat5e cable. Designed for flexible networking applications. 1000ft, LSZH Jacket, 26AWG, and shielded for EMI protection



Search
[78AH6807 at newark.com](#)

ETHERLINE® TRAY CAT.7



Etherline® 2170472 Cat.7 cable designed for stationary applications with performance and maximum transfer rate (IEEE 802.3). PLTC, Ethernet/IP. 1000ft, 22AWG, and shielded (IEC 61156-5)



Search
[78AH6810 at newark.com](#)

Belden 10GXW Category 6A Copper Cable



Belden's newest cable, 10GXW, is the industry's smallest-diameter Category 6A cable designed for smart building and multi-gigabit applications 10GXW13 0051000 is 1000ft, 23AWG, Green Jacket



Search
[41AH9216 at newark.com](#)

Belden RS-485 Direct Burial Cable 3106DB 0101000



Belden® Classics Cables provide best in class performance for a wide range of applications: Video, Sound, Security, Industrial and Interconnect



Search
[41AH7736 at newark.com](#)

ETHERLIN® TRAY CAT5e



Etherline® 2170299 is a 4 pair Cat5e cable. Designed for flexible networking applications. 100ft, LSZH Jacket, 26AWG, and shielded for EMI protection



Search
[78AH6805 at newark.com](#)

ETHERLINE® TRAY CAT.7



Etherline® 2170472 Cat.7 cable designed for stationary applications with performance and maximum transfer rate (IEEE 802.3). PLTC, Ethernet/IP. 100ft, 22AWG, and shielded (IEC 61156-5)



Search
[78AH6808 at newark.com](#)

Browse Our Expanded Selection of Wire & Cable



Newark adds new Wire & Cable every month. Check our portfolio at [newark.com/cable-wire-cable-assemblies](#)



Search
[Wire/Cable at newark.com](#)



PANDUIT®

Transportation Solutions that Surpass Critical Quality and Safety Standards

Find more transportation tooling solutions at www.newark.com/panduit



BMP21-PLUS Camo Portable Label Printer - Limited Edition



Sport your love of the outdoors at home or on the job site with the TOUGH on the outside, SMART on the inside BMP® 21-PLUS Camo Label Printer.

Search
[92AH7472 at newark.com](#)

3M Cable Tie, Natural, 6", 18 lb



Science.
Applied to Life.™

3M Cable Ties secure wire bundles and harness components quickly, without slipping. Curved tip allows for faster threading and installation. Made in the USA.



Search
[61T4037 at newark.com](#)

EMI/RFI Shielded Heat Shrink in 12 inch sticks

ECCO's ShrinkMate™ heat shrink tubing uses MIL-I-23053/5 polyolefin tubing and a highly conductive Polymer Thick Film silver inner coating. The coating shrinks with a heat gun to protect any signal interference on your wire.



Search
[85AC1132 at newark.com](#)

Plastic Snap Rivets



Plastic snap rivets are easily installed with the push of a finger. Holds materials in place. A great alternate to screws and nuts



Search
[28AH1291 at newark.com](#)

BMP51 Label Printer Voice and Data Communications Starter Kit



The BMP® 51 Printer and Voice/Data Label Supply Kit includes BMP® 51 Printer, cable flags, punch block & patch panel labels, faceplate & outlet labels and more




Search
[89T4131 at newark.com](#)

3M™ Cable Tie Base 06299, Screw Mount, Natural/Nylon

Cable tie mounting base makes mounting wires and cables quick, easy and secure; Features self-adhesive stick for lightweight applications or screw mount for heavyweight applications, available in neutral or black



Science.
Applied to Life.™



Search
[96B9181 at newark.com](#)

FIT® Heat-Shrink Tubing F2211/2 BK105

Alpha Wire's FIT® heat-shrink tubing offers a reliable way to protect and seal terminations, providing insulation, moisture and environmental protection, and ruggedness to withstand demanding conditions.



Search
[85K9548 at newark.com](#)

Wire Harness P Clips



Wire harness clips are securely fastened with a screw. Cables can be installed and removed after mounting.



Search
[28AH1321 at newark.com](#)

BMP21-PLUS Printer with BradyGrip Print-on Hook Material



Get everything you need to complete your wire and cable bundle identification with the BradyGrip™ introductory kit with VELCRO® Brand One-Wrap® Material



Search
[83AH8661 at newark.com](#)

EMI/RFI Shielded Heat Shrink in 12 inch sticks

ECCO's ShrinkMate™ heat shrink tubing uses Medical Grade polyester tubing and a highly conductive Polymer Thick Film silver inner coating. The coating shrinks with a heat gun to protect any signal interference, your wire.



Search
[85AC0999 at newark.com](#)

FIT® Heat-Shrink Tubing F2213/16 BK063

Alpha Wire's FIT® heat-shrink tubing offers a reliable way to protect and seal terminations, providing insulation, moisture and environmental protection, and ruggedness to withstand demanding conditions.



Search
[86K1446 at newark.com](#)

Twist Locks



Twist locks are an ideal way to bundle cables and hoses. They are easily removable and reusable by twisting the ends together



Search
[28AH1313 at newark.com](#)

Nylon P Clamps



Nylon P Clamps are an ideal way to route cables and hoses. Sturdy screw mount application.



Search
[28AH1238 at newark.com](#)



TE Connectivity P-Clamp



Enabling Next Generation Assembly – Quick Install, Flexible Design, Ergonomic ·The new “tool-free” large in wire and cable management ·Military, Aerospace, Industrial applications

Search
[40AH2025 at newark.com](#)

TE's SBP Self Laminating Wrap Around/Flag Labels



Self-laminating – protects the printing from chemicals and frequent handling, UL listed, Excellent conformability to irregular surfaces, Withstands exposure to oil, solvents and water, Operating temperature range -40°C to +110°C

Search
[94AC4952 at newark.com](#)



Cable Tie



Cable Tie Mount



Grip Cable Tie



Cable Tie, Nylon 6.6 (Polyamide 6.6), Natural, 100 mm, 2.5 mm, 22 mm, 18 lb



Adhesive 4-Way Entry Cable Tie Mount, Nylon 6.6 (Polyamide 6.6), 19 mm x 19 mm



Hook & Loop Fastener, Grip Tie, PA6/PE, 8 ", 203.2 mm, 0.5 ", 12.7 mm, Black



Search
[75Y3569 at newark.com](#)

Search
[75Y1338 at newark.com](#)

Search
[75Y1011 at newark.com](#)

TMS-SCE Printable Heat Shrink Tubing



TE's SBP Self Laminating Wrap Around/ Flag Labels



Panduit Cable Tie Mount



3:1+ 2:1 shrink ratios, Quick recovery for heat sensitive areas, Lightweight, UL recognized, High quality Military specified meeting the performance requirements of SAE-ASM-DTL-23053/5 class 1. Operating temperature range -55°C to +135°C



Self-laminating – which protects the printing from chemicals and frequent handling, UL listed, Excellent conformability to irregular surfaces, Withstands exposure to oil, solvents and water, Operating temperature range -40°C to +110°C



Panduit TM3S10-M0 Screw Applied Cable Tie Mounts offer a through hole in the mount in which a screw or rivet can be secured, this offers maximum stability for cable bundles.



Search
[41M0777 at newark.com](#)

Search
[94AC4952 at newark.com](#)

Search
[97B2972 at newark.com](#)

Panduit Dome-Top Barb Ty



Panduit Cable Management Tool



The BT3S-M0 Dome-Top® barb ty, features a unique patented design with its round smooth edges.



The GTS-E Ergonomic Cable Tie Hand Tool is easy to operate and has tool-controlled tension that provides a flush cut-off and speeds up installation to lower installed cost.



Search
[14C7445 at newark.com](#)


Search
[79Y3571 at newark.com](#)



THE LARGEST SELECTION OF RACK MOUNT ACCESSORIES

Hammond has over 20 million dollars of in-stock inventory and over 16,000 unique product skus to choose from.

See the full list of accessories at www.hammondmfg.com.



Vented Plastic Snap-Fit Enclosure

Miniature snap-fit plastic enclosure comes with vents to allow the environment in but keep hands out. Perfect for sensors / IoT connectivity. Quick assembly and easy wall-mounting



Search
[84AC4153 at newark.com](#)

Vertical 19" Rack Wall Mount Bracket, 4U

Vertical wall mount bracket allows for quick installation of rack-mounted networking equipment without taking up too much space. Vertical installation of equipment is perfect for small areas like closets



Search
[05T6290 at newark.com](#)

NMB Expanded PWM Offering Now In Stock!

A new series of high performance, 4 wire, PWM driven fans with tachometer signal. These new NMB cooling fans offer high torque, efficient motor technology and aerodynamic impeller design to provide years of performance



Search
[88AH5910 at newark.com](#)

SDU Series, Direct Current Uninterruptible Power Supply (DC UPS) System

The SDU DIN Rail DC UPS is an advanced 24 Vdc uninterruptible power system. A Panel Mount Battery Module #SDU10-24BAT can be purchased separately



Search
[60M3378 at newark.com](#)

Millenium Evo Starter Kit

Millenium Evo unit, interface and bluetooth receiver all in one kit. Connect via Smartphone or PC



Search
[58AC7779 at newark.com](#)



Dual Door IP66 hinged water-tight ABS Plastic Enclosure

Indoor IP66 ABS water-tight enclosure with convenient preinstalled large clear door and panel on cover. Perfect for viewing displays or adjusting internal equipment. Continuous gasket on both doors



Search
[22AJ1446 at newark.com](#)

HOL-SEALERS™ Hole Seal

Seal extra pushbutton holes, conduit openings and knockout openings against dust, dirt, oil and water with this steel hole plug ideal for 3/4-inch conduit holes



Search
[19M8325 at newark.com](#)

NMB Expanded PWM Offering Now In Stock!

A new series of high performance, 4 wire, PWM driven fans with tachometer signal. These new NMB cooling fans offer high torque, efficient motor technology and aerodynamic impeller design to provide years of performance



Search
[88AH5906 at newark.com](#)

Color Keyed Automotive Blade Fuse Holders

THM mountable fuse holders for Low Profile/large Auto blade fuses. Rated for 20 AMPs, 500 VAC. Black housing, PN 3557-2, colors available to match fuses for easy PCB identification



Search
[22M2712 at newark.com](#)

Industrial Edge Smart Controller for Industry 4.0

Powered by an industrialised Raspberry Pi and Arduino. Multiple connections, built in UPS for power management. Wide operating temperature range -25°C to +80°C/-13°F to +176°F and 5-30VDC dual power input



Search
[94AC8719 at newark.com](#)



All Plastic IP66 Water-tight ABS Enclosure

Indoor UL94-HB ABS all-plastic box for wet/dirty/corrosive environments indoors. Fully gasket and ships assembled. Wall mount hardware included. Optional internal shelves and clear lids available



Search
[73R7994 at newark.com](#)

H2Omit Vent Drains, Stainless Steel

H2OM IT Vent Drains allow accumulated water to drain out the bottom of an enclosure



Search
[15R3393 at newark.com](#)

AC Axial Circular Fan

115VAC high speed Axial Fan with 2-ball bearing and wire leaded power connection. High quality aluminum die casting 254mm x 89 mm frame with glass fiber impeller



Search
[58P0936 at newark.com](#)

Carling C-Series Conquers High Amp & Voltage in Compact Size

Compact yet robust, this two-pole circuit breaker with UL489 approval goes up to 15 amps for 120/240 AC. Ideally suited for keeping equipment running and protected



Search
[90B7099 at newark.com](#)

All-Purpose Emergency Stop Switch and Enclosure for Industrial Environments

The plug-and-play design is ideal for industrial environments that includes emergency stop functions and enclosure for all types of machinery or industrial automation applications



Search
[69AC4531 at newark.com](#)



SELECTION SETS US APART

Since first introducing the original Chassis Trak® slide more than 60 years ago, General Devices has engineered thousands of slide solutions. Today, design engineers can choose from the most complete selection of standard and custom slides available from one single source.

SOLID BEARING SLIDES – rugged and cost effective slides for periodic maintenance

ROLLER BEARING SLIDES – reduced push-pull force for heavier loads

BALL BEARING SLIDES – quiet, smooth travel for high cycle applications

BOTTOM MOUNT SLIDES – space saving, heavy duty capacities up to 1,500 lbs.

CUSTOM SLIDES OF ALL KINDS – for applications from rack mount electronics and computer equipment to emergency vehicles, mobile work trucks, and broadcast vehicles.

MORE SLIDES ... FOR MORE SOLUTIONS ... TO MORE APPLICATIONS ... FOR MORE OPPORTUNITIES.

**BOTTOM MOUNT
SLIDES**

**BALL BEARING
SLIDES**



**GENERAL
DEVICES**

Electronic Hardware
Manufacturers

CHASSIS TRAK
Telescopic Slides

VENT RAK
Cabinets & Enclosures

General Devices Company
P.O. Box 39100
1410 S. Post Road
Indianapolis, IN 46239-0100
Made in U.S.A.
Phone: 317-897-7000
Fax: 317-898-2917
www.generaldevices.com



**SOLID/ROLLER
BEARING SLIDES**

CABINETS/ACCESSORIES



SWITCHES & SENSORS

Series 56 Universal Switch - Sealed Switch with Large Actuation Surface

Series 56 Universal Switch include: Sealed - both front and back, Large actuation surface and various front bezel colors, Low mounting depth, large ISO 7000 symbols

eao



IAR series Low Profile Pushbutton Switches for Harsh Environments

IP67 rated with front of panel seal and ensuring high resistance to frost and external contaminants. The actuator material provides a soft feel and allows easy operation even with gloved hands.

APEM
an EPC company



M30 Flat Pushbutton

Eaton's M30 line of pushbuttons and indicating lights look sleek on OEM machines. The large face and steel bezel complement a machine's design. With NEMA 4X and 13 ratings as well as IP66 rated.

EATON



Search
[37AJ8736 at newark.com](#)

HD1 SERIES SEALED MICRO SWITCH

A small-footprint switching Slow-action mechanism enables compact switch footprint and design.

Honeywell



Search
[34K0594 at newark.com](#)
TL3145 Series Long Life Tact Switch

Medium-size Tact Switch features 2 different actuator heights, 3.5mm & 5.2mm. Choose from 3 different actuation forces. The 350gf & 260gf have a life cycle of 500,00 cycles, while the 180gf has an incredible 3,000,000 cycles.

E-SWITCH



Search
[65AC7174 at newark.com](#)
RTDM12 Compact RTD Temperature Sensors

This compact RTD probe has mounting thread and M12 connector for a secure connection that will not separate when pulled. Useful where dependable readings are necessary, such as in the medical, aircraft and automotive industry.

OMEGA



Search
[21AJ9300 at newark.com](#)

Inline Flow-Through Temperature Sensor

Thermometrics Inline Flow-Through Temperature Sensors monitor the temperature of a fluid that passes through it for industrial and automotive applications such as battery pack coolant, HVAC Water management etc.

Amphenol
Advanced Sensors



Search
[80AH1421 at newark.com](#)
PX119-150AI - Pressure Sensor

The PX119 pressure transmitter series is ideally suited for material handling, industrial and mobile equipment applications where space constraints require a small body size.

OMEGA



Search
[58AH0438 at newark.com](#)
ABP2 SERIES Board Mount Pressure Sensors

ABP2 Series are piezoresistive silicon pressure sensors offering a digital output for reading pressure over the specified full scale pressure span and temperature range.

Honeywell



Search
[21AJ7167 at newark.com](#)

B5L Time of Flight Sensor

Real time 3D Sensing of distance to humans or objects. Allows measuring even in bright places.

OMRON
Sensors



Search
[39AH3922 at newark.com](#)
E2EX3 Proximity Sensor

Latest generation sensing distances that significantly reduce target contact. Solve size limited applications with smaller form factor sensors, has oil resistance in harsh cutting environments, and provides real-time condition monitoring.

OMRON



Search
[76AH8157 at newark.com](#)
SmartSolutions™ Starter KitHVAC Monitoring

The turn-key, essential solution to kick-start predictive maintenance initiatives. The HVAC StarterKit has all the essential sensors you need to monitor the critical components of your HVAC unit.

BANNER



Search
[88AH5085 at newark.com](#)

T30R Radar Sensor

A longer-range alternative to ultrasonic sensors, and provides more reliable detection and position feedback in extreme outdoor conditions and other challenging environments. Features a shorter dead zone & better accuracy.

BANNER



Search
[90B2813 at newark.com](#)
CA30 Capacitive Proximity Sensors

Increased immunity to electromagnetic interference (EMI), especially to frequency drives. Also increases the immunity to humidity and dust

OMRON



Search
[84AH2114 at newark.com](#)
PM2.5 Dust, CO2 & RH Air Quality Evaluation Board

Telaire AAS-LDS-UNO Evaluation Board is used to evaluate Telaire air quality sensors including SM-UART-04L PM2.5 laser dust sensor, T9602 temperature & humidity sensors, T6713 CO2 sensor

Amphenol
Advanced Sensors



Search
[13AJ4328 at newark.com](#)

Search
[45Y0753 at newark.com](#)

Search
[92AH7212 at newark.com](#)



Cisco Catalyst IE3400 Heavy Duty Switch

Cisco
Partner

The Cisco® Catalyst® IE3400 Heavy Duty Series -- next-generation, IP67-rated switching platform designed to provide enhanced network-based security, segmentation, and visibility in the most demanding industrial environments.

Search
[80AH9560 at newark.com](#)

JETCON and JETNET Ethernet Switches

korenix

The slim-sized design makes it an ideal model that would physically fit in a network environment with limited space. Require no user setup and immediately start operating as soon as you power it up.

Search
[15AJ5963 at newark.com](#)



RM1D DC switching solid state relays



7S SERIES Relay module with forcibly guided contacts



DG57 General Purpose or Automotive Relay



The ideal solution when switching response times, from ON to OFF and vice versa, are critical to the application. Being fully solid state, the RM1D is the obvious choice for applications necessitating high of switching cycles.



For safety applications, with class A forcibly guided contact relays



Ideal for DC Motor Control with good inrush current capability



Search
[89AH2321 at newark.com](#)

34 SERIES Ultra-Slim electromechanical PCB relays



Search
[76AC0144 at newark.com](#)

Series 586 D.C. Power Contactor



Search
[77AH7056 at newark.com](#)

7L Series New LED Panel Light



Ultra-slim 1 Pole - 6 A relay Printed circuit mount- direct or via PCB socket 35 mm rail mount- via screw, screw less or push-in terminal sockets



The 586-902 is a 1-pole Contactor with large bracket, 200A contact current rating, 12VDC coil voltage and flange mount. SPST-NO contact configuration 21? Coil resistance at 25°C temperature, Continuous duty cycle.



LED light for electrical panels - with magnetic mount. "Two in One" mount - direct magnetic mount or through a screw-mounted metallic bracket. Brightness levels: 600 or 1200 lumens.



Search
[26M7137 at newark.com](#)

5FE Unmanaged Ethernet Switch



Search
[35M1913 at newark.com](#)

USB 2.0 Serial Converter



Search
[24AJ5700 at newark.com](#)

Browse Our Expanded Selection of Relays



The EKI-2525 is a 5-port, unmanaged, industrial switch. It supports 10/100 Mbps Auto-Negotiation, is a compact size with DIN-rail/Wall mount, and has IP30 metal housing.



Easy to set up with plug in terminal block on RS-422/485 side and a high retention USB connector. Supports long range, multi-drop communications.



Newark adds new Relays every month. Check our portfolio at [newark.com/switches-relays](#)



Search
[92Y4736 at newark.com](#)

Search
[94Y7413 at newark.com](#)

Search
[RELAYS at newark.com](#)

TOOLS & PRODUCTION SUPPLIES

91-6832-01 large BENCHTOP BLOWER, 240VAC

The Model 6832 provides reliable, fast static charge control for benchtop work areas or mounted in confined spaces, allowing optimal electrostatics management that minimizes cost and maximizes protection for ESD-sensitive areas.

Search
[52AH2707 at newark.com](#)

Static Shielding Bag 1000 Series

Static Shielding bags are designed to provide a static safe environment for ESD sensitive electronic devices



91-PC2-US-01H AIR BLOWER IONIZER, BENCHTOP, 120VAC

The new Aerostat PC2 provides complete mini-environment ionization protection. Offers outstanding charge neutralization for targeted mini environments and has sufficient air velocity to provide static control up to 4 feet.

Search
[52AH2704 at newark.com](#)

19240 LED ESD Tester

The Desco Testers verify the functionality of an operator's wrist strap and footwear



91-XC2-US-05HA Ionizer, Benchtop, Extended Coverage, Alarm, 120 V

Simco-Ion's new Aerostat XC2 provides complete wide area ionization protection. The XC2 offers outstanding coverage for larger areas with <12 second discharge times at 6 feet (1.8m) distance from the face of the blower.

Search
[72AC8591 at newark.com](#)

EPT250I-A Torque Wrench, Click, Adjustable, Bi- Directional, 3/8", 50- 250in.lb

Adjustable torque wrench with a square drive. Bi-directional ratchet head. Mountz torque drivers and wrenches meet or exceed the accuracy and repeatability requirements of ISO 6789:2003 (6% of setting).



Search
[39M3795 at newark.com](#)

45-091 Wire Stripper, Stripmaster®, 18-10 AWG / 22.225mm PVC Insulation Wires

One-step stripping enhances productivity. Precision-ground, knife-type blades provide clean, accurate stripping



Search
[61H5994 at newark.com](#)

D213-9NE Plier, Side Cutting, Cross-Hatched Serrated Jaw, Sure-Grip

Klein Tools makes some of the world's finest pliers. These High-Leverage, Side-Cutting Pliers features a rivet closer to the cutting edge which provides 46-Percent more cutting and gripping power than other pliers.



Search
[89Y7535 at newark.com](#)

00D SA Tweezer, Precision, Serrated, 120 mm, Stainless Steel Body & Tip

A 120mm high precision Serrated tip and grip Tweezer with anti-magnetic and anti-acid stainless steel body and tip, handcrafted to perfect tip symmetry and balance, polished edges, superior no-scratch/antiglare satin finish.



Search
[94F4979 at newark.com](#)

5056490001 Screwdriver Set, Tool-Check, 39 Piece

28 bits, 1 hand holder 813 suitable for the attachment of bits with 1/4" hexagon drive as per DIN 3126-C 6.3 (ISO 1173) and Wera connection series 1. See all details online at newark.com/31AC4765



Search
[17C1479 at newark.com](#)

309 Bench Vise, 6.25" Jaw Opening, 1.5" W

PanaVise vises and work holding devices are perfect for hobbies and crafts, industry, electronics, wood working and wood carving, small home repair and any work bench environment.



Search
[34M9051 at newark.com](#)

CF-100 Cable Management Tool, Wireless, Inspection Camera & Cable Pulling Tool

Ferret Lite - multipurpose wireless inspection camera & cable pulling tool designed and engineered by Ferret Tools, is a general-purpose inspection camera that allows you to see inside hard to reach locations.



Search
[31AC4765 at newark.com](#)

500-159-30 Digital Caliper, Absolute, 6"

The 500-159-30 is a 0 to 6-inch Absolute Digimatic Calliper with ±0.001mm accuracy. The slider configuration features an ergonomic, thumb-friendly shape.



Search
[27AJ4168 at newark.com](#)

26501-LED Magnifier, 2.25X, Magnification

A ProVue LED Magnifying Lamp with 45 SMD LED lights, 2.25x (5-diopter) magnifying lens mounted in a metal housing and 45-inch spring balanced arm with clamp. Features a 5-inch crystal clear 5-diopter (2.25x) glass lens.



Search
[13AJ1782 at newark.com](#)

170162 Safety Sign, Coronavirus General Safety Information

Safety and social distancing signs for COVID 19. Various COVID 19 signs, colors, dimensions and materials to post all throughout public and private facilities.



Search
[45X8736 at newark.com](#)

Search
[05R8918 at newark.com](#)

Search
[68AH8419 at newark.com](#)

**DeoxIT® Gold G-Series
Contact Enhancer
Conditioner & Protector
Spray**

A unique Contact Cleaner for plated metal surfaces. It has comes with stainless steel extension tub. Improves conductivity, maintains optimum signal quality, reduces fretting and dendrite corrosion and stabilizes connections.



**100ct 99.8% Isopropyl
Alcohol Cleaning Wipes**

Comes in a pop-up-tub featuring pure anhydrous (containing the least water possible and no denaturant) isopropyl alcohol is excellent for tape head cleaning, defluxing, stencil cleaning, other light cleaning and as a flux thinner.



**Isopropyl alcohol (IPA) wipes
– 70%, 50 pack**

Convenient, low-linting wipes are pre-saturated with 70% pure IPA. · Ideal for electronics cleaning · Plastic-safe · Lint-free & tear resistant



Search
[42J5221 at newark.com](#)

Search
[25C4466 at newark.com](#)

Search
[94AH5983 at newark.com](#)

**Optic Prep™ Presaturated
Wipe 50 pack**



CP410 is a Cleaner Wipe, high quality pre-moistened lens-grade tissues for cleaning optical surfaces, these highly effective cleaning wipes are ideal for cleaning and polishing optical surfaces, lenses, photographic equipment, etc.

**Electro-Wash® MX Cleaner
Degreaser Pre-Saturated
Individual Wipe**

High flash point cleaner that quickly removes soils, adhesives, and residues from insulation jackets and conductors on Telecom, fiber optic and coaxial cables.



Ultrasonve Cleaning Solvent

ULS is a fast-drying solvent specially formulated for the quick and efficient cleaning of electrical equipment. It offers excellent degreasing properties and a fast evaporation rate



Search
[00Z1512 at newark.com](#)

Search
[31Y0740 at newark.com](#)

Search
[49AH7293 at newark.com](#)

EZ-RJPRO™ HD Crimp Tool



Designed for the professional installer with a ratcheted, high leverage, ultra stable platform for consistent, repeatable terminations. Crimp cables with larger jacket and conductor OD's ensure every termination will meet FCC specifications.

**100pk EZ-RJ45 Cat 6+
Connectors**

For use in Cat 6 compliant data networks. Category 6 performance per EIA/TIA B. 2. FCC compliant, UL rated. RoHS compliant EZ to verify wire sequence. Simple one piece design.. no bars or liners.



**100pk EZ-RJ45 Cat5e
Connectors**

Use in category 3, 5, 5E compliant data networks.100 Pack in Jar. Thru holes allow wire pairs to be inserted thru front of connector for faster terminations. Works with solid or stranded wire.



Search
[06AC3903 at newark.com](#)

Search
[26Y8547 at newark.com](#)

Search
[06AC3903 at newark.com](#)

**Converter Switch, Media,
10/100 Mbps Copper To 100
Mbps Fiber, 40 KM**



Bring fiber to the desktop more conveniently and at a lower cost than installing fiber NICs ; measures just 0.8"H x 1.8"W x 3.4"D.Powered by a universal AC power supply or the optional rackmountable PowerTray.

**Media Converter Switch,
10/100Mbps Copper to
100Mbps Fibre, Multimode**

RJ-45 ports support autonegotiation, to easily attach any 10- or 100-Mbps device. ST, SC, MT-RJ, and LC fiber port types available. Function as both a media converter and a switch. Withstands temperatures of 32° to +104° F (0° to 40° C).



**LBH3080A 8-Port Industrial
Fast Ethernet Switch**



Ideal for use in harsh environments. Supports multiple industries of Security/ surveillance to process IP camera data, Building automation and HVAC control, M2M communications with remote stations in oil/gas facilities.

Search
[53Y4174 at newark.com](#)

Search
[36J9721 at newark.com](#)

Search
[44AC0865 at newark.com](#)

**LBH240A-H-ST Heavy Duty,
4 x 10/100 Copper, 2 x Fibre
Ports Switch**



Compact industrial Fast Ethernet switch with 4 10/100 Mbps RJ45 ports and 2 100BASE-FX ports. Features panel mounting with 100-240VAC input.

**Extender Kit, KVM over
Ethernet, USB VGA over
CAT5**

ODT60001 is a 500ft USB VGA over CAT5 UTP KVM Console Extender Kit versatile, plug and play solution, opens up options by enabling an extended physical separation between a KVM workstation and a computer or KVM switch.



**Extender Kit, USB over
Ethernet, Dual CAT5/CAT6,
Transmitter & Receiver**



B202-150 is a 150ft 1-port USB over CAT5/6 Extender with transmitter and receiver. It allows to connecting computer to an USB 1.1 peripheral up to 150ft away using ordinary CAT5/CAT5e/ CAT6 cable. Bus-powered.

Search
[53K8227 at newark.com](#)

Search
[62W1504 at newark.com](#)

Search
[99R9964 at newark.com](#)

BENCH TEST INSTRUMENTS

NGU401 Source Measure Unit – Bundle

The four-quadrant NGU401 Source Measure Unit is the semiconductor testing specialist for general-purpose applications that span many industries and many different devices under test.

RODELSCHWARZ
More than just a test



Infiniium EXR Series Digital Oscilloscope



15.6" Full HD Touchscreen Display
– 500MHz bandwidth with four analog and 16 digital channels



Infiniium EXR Series Digital Oscilloscope



15.6" Full HD Touchscreen Display
– 500MHz bandwidth with eight analog and 16 digital channels



Search
[13AJ3128 at newark.com](#)

Infiniium EXR Series Digital Oscilloscope



15.6" Full HD Touchscreen Display
– 1GHz bandwidth with four analog and 16 digital channels

Search
[83AH8978 at newark.com](#)

Infiniium EXR Series Digital Oscilloscope

15.6" Full HD Touchscreen Display
– 1GHz bandwidth with eight analog and 16 digital channels



Search
[83AH8979 at newark.com](#)

QXP750SP Single Output 750W Programmable Power Supply



Designed to provide flexibility in the choice of voltage and current so as to meet multiple diverse applications. Adjustable to 80VDC and 50A within a defined power envelope.

Search
[83AH8980 at newark.com](#)

CPX400SP Single Output 420W Variable Power Supply



Provides flexibility in a compact package. Adjustable to 60VDC and 20A within a defined power envelope. RS-232, USB, LAN and GPIB Interfaces.

Search
[83AH8981 at newark.com](#)

EX354RD Dual Output 280W Variable Power Supply

Provides flexibility in a compact package. Adjustable to 35VDC and 4A within a defined power envelope.



Search
[24AJ5491 at newark.com](#)

PL303 Single Output High Precision Power Supply



Provides flexibility in a compact package with ability to control output resolution to 0.1mA. Adjustable to 30VDC and 3A for 90W total output.

Search
[04X9895 at newark.com](#)

PL303QMD Dual Output 180W Tracking Power Supply



Dual outputs, each adjustable to 30VDC and 3A. Quad modes include Independent, Parallel, Isolated Tracking and Isolated Ratio Tracking modes.

Search
[04X9910 at newark.com](#)

MX100TP Triple Output 315 Watt Programmable Power Supply

Three outputs, each provide up to 35VDC/3A. Unique range switching, CH1 and CH2 can provide 16V/6A as an alternative and CH3 can provide 70V/1.5A. High setting resolution down to 1mV and 0.1mA.



Search
[04X9985 at newark.com](#)

MX180TP Triple Output 375 Watt Programmable Power Supply



Three outputs, two provide up to 30VDC/6A, the third up to 5.5VDC/3A

Search
[04X9988 at newark.com](#)

TGP110 10MHz Pulse Generator



Dedicated pulse generator enables pulses of a set width regardless of the repetition rate, offering duty cycles which can extend down to 1 in 100 million. DC-10MHz, min pulse width >30nS.

Search
[46Y2847 at newark.com](#)

TGF4042 Two Channel 40MHz Function Generator

A frequency capability of up to 240MHz is combined with two identical full performance channels that can operate as independent generators or in coupled or tracking modes.



Search
[71Y6988 at newark.com](#)

PSA1302USC Handheld Spectrum Analyzer



Powerful yet compact analyzer provides frequency range of up to 2.7GHz with resolution bandwidths of 1MHz, 280KHz or 15KHz. Includes carry case and accessory pack.

Search
[06X3421 at newark.com](#)

Search
[83AC7334 at newark.com](#)

Search
[63W2663 at newark.com](#)



DMM6500 Bench Digital Multimeter



DAQ6510 Bench Data Acquisition Unit



DAQ970A Data Acquisition Unit



Precision DMM delivers high functionality and best-in-class measurement insight. Large 5-inch touch screen display, expanded measurement ranges of 10pA-10A and 1mΩ to 100MΩ



Precision data acquisition and logging system features two slots and 12 plug-in switching and control modules available. Create a test system able to measure or control up to 80 devices under test



Three-slot mainframe with built-in 6½ digit DMM accepts eight switch and control plug-in modules. Measures and converts 12 different input signals



Search
[51AC7032 at newark.com](#)

DAQ973A Data Acquisition Unit with GPIB Interface



Search
[51AC7225 at newark.com](#)

Model 2450 SourceMeter® SMU Instrument



Search
[72AC4094 at newark.com](#)

70MHz 2CH Digital Storage Oscilloscope



Three-slot mainframe with built-in 6½ digit DMM accepts eight switch and control plug-in modules. Measures and converts 12 different input signals



Precision instrument boasts a 5" capacitive high resolution touch screen and combines the capabilities of analyzers, curve tracers and I-V systems, at a fraction of the cost



Offers 9" WVGA display, 5m point record length and 2 GS/s sample rate. TekVPI® probe interface also supports traditional passive BNC probes



Search
[52AH3548 at newark.com](#)

70MHz 4CH Digital Storage Oscilloscope



Search
[88W3815 at newark.com](#)

100MHz 2CH Digital Storage Oscilloscope



Search
[54AH1530 at newark.com](#)

100MHz 4CH Digital Storage Oscilloscope



Offers 9" WVGA display, 5m point record length and 2 GS/s sample rate. TekVPI® probe interface also supports traditional passive BNC probes.



Offers 9" WVGA display, 5m point record length and 2 GS/s sample rate. TekVPI® probe interface also supports traditional passive BNC probes.



Offers 9" WVGA display, 5m point record length and 2 GS/s sample rate. TekVPI® probe interface also supports traditional passive BNC probes.



Search
[54AH1536 at newark.com](#)

200MHz 2CH Digital Storage Oscilloscope



Search
[54AH1542 at newark.com](#)

200MHz 4CH Digital Storage Oscilloscope



Search
[54AH1548 at newark.com](#)

50MHz 2CH Digital Storage Oscilloscope



Offers 9" WVGA display, 5m point record length and 2 GS/s sample rate. TekVPI® probe interface also supports traditional passive BNC probes.



Offers 9" WVGA display, 5m point record length and 2 GS/s sample rate. TekVPI® probe interface also supports traditional passive BNC probes.



The TBS1000C Series offers affordable performance and is designed to meet the needs of today's educational institutions, embedded design engineers, and maker community.



Search
[54AH1554 at newark.com](#)

70MHz 2CH Digital Storage Oscilloscope



Search
[54AH1560 at newark.com](#)

100MHz 2CH Digital Storage Oscilloscope



Search
[77AH8527 at newark.com](#)

200MHz 2CH Digital Storage Oscilloscope



The TBS1000C Series offers affordable performance and is designed to meet the needs of today's educational institutions, embedded design engineers, and maker community.



The TBS1000C Series offers affordable performance and is designed to meet the needs of today's educational institutions, embedded design engineers, and maker community.



The TBS1000C Series offers affordable performance and is designed to meet the needs of today's educational institutions, embedded design engineers, and maker community.



Search
[77AH8528 at newark.com](#)

Search
[77AH8529 at newark.com](#)

Search
[77AH8530 at newark.com](#)

FIELD INSTRUMENTATION

ii910 – Sonic Industrial Imager

FLUKE.

Quickly pinpoint the location of compressed air and vacuum leaks as well as corona arc. Increase safety while reducing capital expense.



Search
[92AH2695 at newark.com](#)

TiS75+ Thermal Imaging Camera

FLUKE.

Fluke TiS75 Infrared camera gives you the flexibility of manual focus to capture the best image possible of your target. 384 x 288 infrared resolution.



Search
[15AJ1856 at newark.com](#)

87V-MAX Heavy Duty Industrial Digital Multimeter

FLUKE.

Provides all of the features and benefits of the industry leading Fluke Model 87V, in a rough environment enclosure. Rated to withstand a 13' drop, IP67 rated case.



Search
[40AH0535 at newark.com](#)

117 Digital Multimeter

FLUKE.

The 6,000 count, True RMS Fluke 117 multimeter is popular in a variety of commercial and educational environments. CAT III 600 V safety rated.



Search
[83K1721 at newark.com](#)

FLUKE-179ESFP Digital Multimeter

FLUKE.

Autorangeing TRMS DMM features include Manual and automatic ranging, frequency, capacitance, resistance, continuity and diode measurements with min-max-average recording.




Search
[25C4804 at newark.com](#)

ii900 – Sonic Industrial Imager

FLUKE.

Quickly pinpoint the location of compressed air and vacuum leaks. Increase efficiency while reducing capital expense.



Search
[01AH3575 at newark.com](#)

Fluke-377 FC Clamp Meter Kit

FLUKE.

True RMS clamp meter uses FieldSense™ technology, allowing non-contact current AND voltage measurements through the clamp jaw.



Search
[15AJ1857 at newark.com](#)

87V Industrial Digital Multimeter

FLUKE.

20,000 count, True RMS Fluke 87V multimeter is designed to handle complex signals and is well suited for most heavy industrial environments.



Search
[96H6287 at newark.com](#)

117/323 Digital Multimeter Kit

FLUKE.

Popular in a variety of industrial and HVAC maintenance applications, this combo set includes the popular Fluke 117 DMM and 323 TRMS clamp meter.



Search
[66W5428 at newark.com](#)

FLUKE-289 Digital Multimeter

FLUKE.

Designed to solve complex problems in electronics, plant automation, power distribution, and electro-mechanical equipment; it is loaded with powerful features so you can solve problems faster and help minimize downtime.



Search
[42M9905 at newark.com](#)

TiS55+ Thermal Imaging Camera

FLUKE.

Fluke TiS55 Infrared camera gives you the flexibility of manual focus to capture the best image possible of your target. 256 x 192 infrared resolution.



Search
[15AJ1855 at newark.com](#)

Fluke-378 FC Clamp Meter Kit

FLUKE.

Provides all of the features and benefits of the 378-FC, plus Power Quality Test feature



Search
[15AJ1858 at newark.com](#)

87V Industrial Digital Multimeter/Insulated Tool Kit

FLUKE.

Field maintenance package includes the highly acclaimed Fluke 875 Multimeter and 8pc 1kV insulated tool kit.



Search
[07AH5513 at newark.com](#)

FLUKE-115 Digital Multimeter

FLUKE.

Displays TRMS voltage and current with 6000 count resolution, continuity and capacitance. Large backlit LCD display allows work in subdued light. Safe use in CAT III 600V Environments.



Search
[83K1718 at newark.com](#)

FLUKE-77-4 Digital Multimeter

FLUKE.

Wide 1000V measurement range, average responding AC measurements, measure 10A, 20A for 30 seconds, also measures resistance, frequency and capacitance.



Search
[18M4542 at newark.com](#)

15.0010 POAG-KBT6DIN Series Test Jack



Right-angled 6mm test socket for self-assembly of connecting leads for potential equalization.



14.0034-21 6mm Banana Test Jack



6mm panel mount jack rated at 600V, 80A, black with silver plated contacts.



04.0058 POAG-S6/25 Series Test Plug



6mm x 40mm test plug for potential equalization made of nickel plated brass.



Search
[40AH1734 at newark.com](#)

22.1053 4mm Banana Test Plug



4mm plug to M4 screw terminal rated at 50A with gold plated contacts



Search
[40AH1729 at newark.com](#)

04.0056 POAG-S6/15 Series 6mm Test Plug



6mm x 30mm test plug for potential equalization made of nickel plated brass.



Search
[40AH1728 at newark.com](#)

CT4446-100 Instrument Grade RF Test Cable Assembly



100cm RG142B/U, 50 ohm double shielded coaxial cable with SMA Male to BNC Male



Search
[40AH1736 at newark.com](#)

CT4442-100 Instrument Grade RF Test Cable Assembly



100cm RG142B/U, 50 ohm double shielded coaxial cable with N-Type Male to N-Type Male



Search
[40AH1727 at newark.com](#)

CT4448-10 BNC to 4mm Banana Jacks Attenuator



Insulated BNC to double 4mm banana jacks attenuator x 10 attenuation



Search
[36AJ5265 at newark.com](#)

CT4448-20 BNC to 4mm Banana Jacks Attenuator



Insulated BNC to double 4mm banana jacks attenuator X 20 attenuation



Search
[36AJ5257 at newark.com](#)

CT4448-100 BNC to 4mm Banana Jacks Attenuator



Insulated BNC to double 4mm banana jacks attenuator x 100 attenuation



Search
[24AJ5663 at newark.com](#)

2894-2 Red Binding Post to Single Banana Plug Adapter



Insulated binding post to 4mm banana plug with center cross hole for side stack-up connection



Search
[24AJ5665 at newark.com](#)

1452 Double Binding Post to BNC Jack Adapter



BNC female to stackable binding post pair rated at 500Vrms hands free operation.



Search
[24AJ5664 at newark.com](#)

1270 Double Banana Plugs to BNC Adapter



BNC male to double 4mm stacking banana plugs rated at 500Vrms hands free operation



Search
[78B1717 at newark.com](#)

72937 BNC Male to Double Banana Jacks



IEC insulated BNC male to double 4mm banana jacks rated at 3A and 500V Cat I, 150V Cat II



Search
[58T2919 at newark.com](#)

4601 Triple Banana Jacks



Insulated triple banana jacks; colors are red, black and green. Rated 15A and 30VAC/60VDC Max hand held operation.



Search
[10M4162 at newark.com](#)

Search
[34M2974 at newark.com](#)

Search
[77B2598 at newark.com](#)

MULTICOMP PRO CONNECTORS & MORE

Sealed USB Panel Mount Connectors

IP67 / IP68 plastic and metal USB 2.0 Type A, USB 3.0 Type A, Mini USB Type B & USB Type C panel mount connectors and cable assemblies.

multicomp^{PRO}



Search
[64AH1283 at newark.com](#)

IP67 Hybrid Connectors

Power and signal connections all in one unit. Simple but robust quick connect and disconnect locking system.

multicomp^{PRO}



Search
[64AH1351 at newark.com](#)

MP-Y13 Bayonet Locking Power Connectors

The MP-Y13 series with IP68 sealing offers up to 13A / 250V, 500 mating cycles and is available with solder or screw termination.

multicomp^{PRO}



Search
[64AH1645 at newark.com](#)

IP68 High Density 15P D-Subs

Waterproof thermoplastic plastic HD-SUB 15 pin connectors and cable assemblies. 500 mating cycles.

multicomp^{PRO}



Search
[64AH1336 at newark.com](#)

Flexible PVC Sleeving

A flexible PVC sleeving in a wide range of sizes, manufactured to meet 105°C applications, supplied on 100 metre / 328 feet continuous coils to facilitate overall protection of cable harnesses.

multicomp^{PRO}



Search
[97K7924 at newark.com](#)

IP68 RJ45 Panel Mount Connectors

Sealed thermoplastic and metal RJ45 panel mount connectors and cable assemblies.

multicomp^{PRO}



Search
[64AH1316 at newark.com](#)

IP67 M12 Push-Pull Connectors

12mm panel cutout size, push-pull coupling, 2-9 poles, rated up to 13A / 250V, 500 mating cycles.

multicomp^{PRO}



Search
[64AH1717 at newark.com](#)

MP-T21 Threaded Power Connectors

The MP-T21 series with IP68 sealing offers up to 30A / 500V, threaded coupling, 500 mating cycles and solder or screw termination options.

multicomp^{PRO}



Search
[64AH1603 at newark.com](#)

Weatherproof Automotive Connector Kits

Multi-ribbed automotive connectors with rubber gaskets which isolate the connection from dust, water, and other contaminants which could damage a connection. Available in 1, 2, 3, 4 and 6 pole variants.

multicomp^{PRO}



Search
[84Y7918 at newark.com](#)

Spiral Wrap

Heavy duty, low density polyethylene spiral wraps designed to bundle & protect the routing of cables, harnesses, and hoses.

multicomp^{PRO}



Search
[70AC8993 at newark.com](#)

IP67 HDMI Panel Mount Connectors

Sealed thermoplastic and metal HDMI panel mount connectors and cable assemblies.

multicomp^{PRO}



Search
[64AH1326 at newark.com](#)

MP-T13 Threaded Power Connectors

The MP-T13 series with IP68 sealing offers up to 13A / 250V, threaded coupling, 500 mating cycles and solder or screw termination options.

multicomp^{PRO}



Search
[64AH1573 at newark.com](#)

MP-Y21 Bayonet Locking Power Connectors

The MP-Y21 series with IP68 sealing offers up to 30A / 500V, 500 mating cycles and is available with solder or screw termination.

multicomp^{PRO}



Search
[64AH1675 at newark.com](#)

Pro-Braid - Metal Screening Braid

Premium performance copper screening braid available with tin or nickel plating

multicomp^{PRO}



Search
[94AC7777 at newark.com](#)

Industrial Ethernet Switches

A range of 5 and 8 port 10/100 and Gigabit Industrial Ethernet Switches. No software required. Simply plug in and connect.

multicomp^{PRO}



Search
[39AH5508 at newark.com](#)

6000 Count Digital Clamp Meter

multicomp PRO



Portable true RMS AC/DC clamp meter with automatic range, designed according to EN61010-1 CAT II 600V / CAT III 300V safety langes, and comes with full-function protection which ensures users a safe and reliable measurement experience.

Search
[13AJ0606 at newark.com](#)

4000 Count Pocket Digital Multimeter

multicomp PRO



Palm size stable and reliable multimeter with 4000 display counts. An ideal tool to measure AC/DC voltage and current, resistance, capacitance, frequency, continuity and diode with overload protection. Complies with CAT III 600V; CE and cETIus certificates.

Search
[90AH9781 at newark.com](#)

100MHz PC Scope with Signal Generator

multicomp PRO



2 channel, 100MHz, 8-bit PC-based oscilloscope with built-in signal generator. Featuring 10M record lengths, friendly UI, multi-trigger options, USB bus powering and an ultra-thin body design with easy portability.

Search
[83AH9507 at newark.com](#)

Wide Range Programmable Power Supply

multicomp PRO



300W, 60V/15A wide range programmable DC power supply.

Search
[42AH2837 at newark.com](#)

ESD Safe Fume Extraction Unit

multicomp PRO



ESD safe bench-top fume extractor can be operated vertically or horizontally, can remove soldering smoke and fumes quickly, safely and quickly. Filter is made of highly activated carbon, strong and absorbent (replacement filters available).

Search
[39AH0171 at newark.com](#)

Pocket IR / Infrared Thermometer

multicomp PRO



Miniature pocket sized IR thermometer offering precise, non-contact temperature measurements. The distance to target ratio (or optics ratio) is 1:1, therefore the thermometer should be positioned as close to the target as possible when measuring.

Search
[32AJ7299 at newark.com](#)

Datalogging Digital Multimeter

multicomp PRO



60000 counts 4 5/6 digits, handheld auto-range true RMS intelligent multimeter. The overall circuit is designed with LSI ADC as the core. The full-range overload protection circuit & design makes it to be a special electrical meter with superior performance.

Search
[90AH9786 at newark.com](#)

80MHz Arbitrary Waveform Generator

multicomp PRO



80MHz, 2-channel arbitrary waveform generator, featuring max 1.25GS/s sample rates, 1Hz frequency resolution, 14-bits vertical resolution and max 1M arbitrary waveform length.

Search
[74AH3015 at newark.com](#)

ESD Safe USB Soldering Iron

multicomp PRO



USB soldering iron especially for precision soldering. From universities to enterprise laboratories this compact soldering unit takes small component disassembly everywhere.

Search
[39AH0167 at newark.com](#)

Outdoor Combo Antennas

multicomp PRO



IP67 Combo Antennas (2xLTE, 1xGPS/GNSS), 698~960MHz / 1710~2170 MHz / 2300~2690MHz, adhesive mount or through hole mount options available with 1.5m or 3m SMA cable assemblies.

Search
[41AH4617 at newark.com](#)

pH Meter

multicomp PRO



Pen-type digital pH meter with a measurement range of 0 to 14.00pH, 0.01pH resolution and ± 0.03 pH accuracy. For use in environments where pH measurements are required, such as aquariums, food processing facilities, photography, pools & more

Search
[32AJ7298 at newark.com](#)

Digital Tachometer

multicomp PRO



Digital tachometer, which can provide fast and accurate non-contact RPM and surface speed measurements of rotating objects. This tachometer uses the CPU, photo-electrical and junction laser techniques for one combined instrument.

Search
[12AJ7215 at newark.com](#)

Linear Bench Top DC Power Supply

multicomp PRO



180W, single-channel, linear benchtop DC power supply with channel outputs of 0-60V / 0.3A x 1CH.

Search
[42AH0484 at newark.com](#)

4-in-1 Multi-function Soldering Station

multicomp PRO



4-in-1 rework station, including functionality for soldering, hot air, desoldering and electronic tweezers. This intuitive station has a high accuracy MCU control which synchronously detects whether the 3x tool channels can be used independently.

Search
[72AC8885 at newark.com](#)

Outdoor Wireless OMNI Antennas

multicomp PRO



IP67/NEMA6 DSRC Urban and LoRa antennas. 7.6 dBi, VSWR: 2.0:1, Linear Polarisation, 50ohm, N Type connector.

Search
[41AH4620 at newark.com](#)

ROBUST PORTFOLIO OF SENSORS & PASSIVE COMPONENTS

SOLVING CUSTOMERS' TOUGHEST CHALLENGES


TT Electronics offers one of the industry's widest portfolios of sensors and power management devices. Our solutions improve the precision, speed and reliability of critical aspects of our customer's applications.

HOW WE HELP OUR CUSTOMERS

- Engineering Expertise
- Speed to Market
- Platform products combined with customized solutions




[Learn More About Our Offering](#)




OPTOELECTRONICS

- Fluid Sensors
- Slotted Switches
- Reflective Sensors
- Non-IR Components
- IR Components
- Optoisolators
- Fiber Optics
- Hall Effect
- VLEDs




POTENTIOMETERS & TRIMMERS

- Panel Potentiometers
- Slide Potentiometers
- Precision Potentiometers
- Hollow Shaft Potentiometers
- Non-Contacting Potentiometers
- Trimmers



ENCODERS

- Metal Shaft
- Plastic Shaft
- Top Adjust
- Side Adjust
- Vertical, Side Adjust



FIXED RESISTORS

- Signal Conditioning
- Power Management
- Circuit Protection
- Current Sense



Tight Tolerance Precision Current Sense Resistors

Tolerance down to 0.5% and TCR values down to 100ppm. Sizes range from 0201 up to 1206.

OHMITE



Metal Element Current Sense Chip

Precision alloy element provides low inductance, low tolerance, and ideal TCR values for current sense applications.

OHMITE



LST Series Metal Oxide Varistors

SPD Thermally Protected Varistor. he built-in thermal disconnecting function and electric arc shield provides additional protection to prevent catastrophic failure and fire hazard even under the extreme circumstances

Littelfuse
Expertise Applied | Answers Delivered



Search
[29AH2742 at newark.com](#)

Internal Wifi Antenna

2400~2483.5MHz/4900~5825MHz., Dual band Frequency, Customizable cable length and type, Rigid PCB Type, RoHS compliant.

nc
NANO CONNECT



Search
[63R6358 at newark.com](#)

Wi-Fi 6/6E Triple Band Embedded Antenna

Supports triple bands, including the 6GHz band. TE's antenna solutions and integration expertise unleash the power of the extensive additional spectrum from Wi-Fi 6E. This additional spectrum enables new applications & greater network flexibility.

TE
TE CONNECTIVITY



Search
[25AJ3861 at newark.com](#)

TCB Conductive Polymer - COTS-Plus

Conductive polymer series designed for use in demanding industrial applications requiring very low ESR with stable, high-frequency CAP retention & longer life performance, such as high power DC/DC converters in telecom, industrial & avionics.

AVX



Search
[28AJ0389 at newark.com](#)

R52 Miniature Class X2 Film Cap

The R52 Series is ideal for harsh environmental conditions and meets the demanding Automotive Electronics Council's AEC-Q200 qualification requirements.

KEMET
KEMET CORPORATION



Search
[82AH5354 at newark.com](#)

SAW/FBAR Filters

TAIYO YUDEN SAW and FBAR RF filters allow for improved signal quality through lower insertion loss for decreased power consumption and high attenuation in 1.8 x 1.4mm footprint.

TAIYO YUDEN



Search
[01AH9107 at newark.com](#)

Surface MLCC; VJ HIFREQ HT SERIES

Surface Mount Multilayer Ceramic Chip Capacitors for High Temperatures 175 °C / 200 °C -Case size 0402, 0505, 0603, 0805, 1111 -High frequency / high temperature 175 °C / 200 °C -Ultra-stable dielectric material

VISHAY



Search
[84AH4485 at newark.com](#)

CH Series Microwave Resistors ; High Frequency Range: up to 70GHz

· Unique design · Real resistance value maintained across frequency range: High Frequency Range: up to 70GHz · Sizes: 02016, 0402, 0603 · Broadband performance · Low parasitics

VISHAY




Search
[19AJ5809 at newark.com](#)

Wirewound , Surface Mount Inductors, IMC-0805 Series

Wirewound Inductor, 22 nH, 0.1 ohm, 3.3 GHz, 600 mA, 0805 [2012 Metric], IMC-0805-01 Series High self-resonant frequency values High Q values at higher frequencies Wirewound construction

VISHAY



Search
[83AH3472 at newark.com](#)

High Power Thin Film Resistor

EIA large size 3216 (1206 in inches) and power rating: 1W. +/-0.5% tolerance and +/-50ppm TCR. Superb reliability and stability

SSM SUSUMU
Thin Film Specialist and Innovator



Search
[15R0731 at newark.com](#)

Short side terminal Current sensing chip resistor

Face down mounting and superb heat dissipation. 22m ohms, 0.5W for 0805 size, +/-1% tolerance, +/-50ppm TCR. Low ESL

SSM SUSUMU
Thin Film Specialist and Innovator



Search
[53K5172 at newark.com](#)

Precision, Reliable Thin Film Chip Resistor

10k ohm, 0603 size, +/-0.1% tolerance, +/-25ppm TCR, Highly reliable, Biased life test 10000 hrs : less than 0.1% drift

SSM SUSUMU
Thin Film Specialist and Innovator



Search
[70AC1143 at newark.com](#)

Browse Our Expanded Selection of Capacitors

Newark adds new Passives every month. Check our portfolio at [newark.com/passive-components](#)

Newark
ELECTRONIC COMPONENTS



Search
[70AC1406 at newark.com](#)

Search
[18X9929 at newark.com](#)

Search
[PASSIVES at newark.com](#)

Kintex UltraScale FPGA KCUI05 Evaluation Kit



PSOC 6 WI-FI Bluetooth Pioneer Kit for IoT



CY4533 Evaluation Kit



The Kintex UltraScale family delivers ASIC-class system-level performance, clock management, and power management for next generation systems at the right balance of price, performance and power.



Low-cost hardware platform that enables design and debug of PSoC 62 MCU and the Murata 1LV module



USB Type-C PD Controller, Barrel Connector Replacement (BCR)



Search
[32AC9663 at newark.com](#)

MCU Development Boards



Search
[66AH9491 at newark.com](#)

PIC16F152 family of 8 bit MCUs



Search
[01AH3203 at newark.com](#)

Silicon Carbide MOSFET, N-Channel Enhancement Mode



High Performance, cost effective
MCU Development Kits



Wide variety of powerful and cost
effective 8 bit MCUs



Compatible with commercial gate
drivers with low conduction losses
at all temperatures with faster
and more efficient switching.



Search
[17AJ3954 at newark.com](#)

Half-bridge 1200 V CoolSiC™ MOSFET Module



Search
[36AJ3970 at newark.com](#)

Ultra-low-power dual core Arm Cortex-M4 MCU



Search
[89AH0975 at newark.com](#)

Low data rate, low power Sub 1GHz transceiver



62 mm 1200 V, 2 m² half-bridge
module with CoolSiC™ MOSFET
with pre-applied Thermal
Interface Material.



64 MHz, Cortex-M0+ 32MHz
with 1 Mbyte of Flash memory,
Bluetooth LE 5.2, 802.15.4,
Zigbee, Thread, USB, LCD, AES-
256



Designed to operate both in
the license-free ISM and SRD
frequency bands at 169, 315, 433,
868, and 915 MHz, but can also be
programmed to operate at other
additional frequencies in the
300-348 MHz, 387-470 MHz, &
779-956 MHz.



Search
[82AH4537 at newark.com](#)

TMC2300-IOT-REF: Open- source reference design for evaluation of TMC2300-LA



Search
[81AH0045 at newark.com](#)

EVAL-IMOTION2GO: Easy introduction to iMOTION™ system, tools and software



Search
[48W6792 at newark.com](#)

MPM3695-25: 16V, 20A, Scalable DC/DC Power Module



Quickly prototype your IoT
applications running on 3.5 – 6 V
batteries.



Starter kit for the first
introduction to the iMOTION™
devices and system.



The MPM3695-25 is a scalable,
fully integrated power module
with a PMBus interface.



Search
[13AJ1411 at newark.com](#)

SMD Reflective Optical Sensor



Search
[92AH4516 at newark.com](#)

Reflective Optical Sensor



Search
[69AH1518 at newark.com](#)

Browse Our Expanded Selection of Semiconductors



The OPB9000 is a versatile
sensor that can be used in a wide
variety of industrial and medical
applications



The OPB9001 PCB module takes
the versatile and programmable
OPB9000 reflective sensor and
enhances its capabilities by
integrating multiple features into
a robust, small form factor for
ease of use.



Newark adds new Semis &
Dev Kits every month. Check
our portfolio at [newark.com/semiconductors-ICs](#)



Search
[17AC5524 at newark.com](#)

Search
[38AH5863 at newark.com](#)

Search
[SEMICONDUCTORS at newark.com](#)

multicomp PRO
The Engineer's Choice



High quality, great value cable sleeving

Select from a wide variety of materials, sizes and types

Designed by our engineers for engineers like you, Multicomp Pro's range of sleeving will provide you with the perfect solution to protect your cables and wires.

Whether you need protection from the most abrasive of environments or you are simply looking to tidy up your cable bundles, Multicomp Pro's range has it all with materials ranging from PVC to Fibreglass and sleeving types from general purpose to fireproof. Whatever your application, think of Multicomp Pro first!

newark.com/multicomp-pro-sleeving

**7x more semis
3x more passives
2x more interconnect**
Fast & free shipping*

Choose from a new and expanded range of board-level components with free shipping on orders over \$150 USD & faster delivery.

SHOP THE WAY YOU PREFER



newark.com
order@newark.com /
quote@newark.com



1 800 463 9275
7:00 a.m. – 8:00 p.m.
M-F (EST)



newark.com/technical-support
1 877 736 4835

E-PROCUREMENT SYSTEMS

We can link with any eProcurement system, and our dedicated e-team will facilitate your implementation. Email: eproc@newark.com

GLOBAL REACH, LOCAL RESOURCES

- 10 million products available, 950,000 in stock
- Supporting 46 websites in 27 languages
- Authorized distributor for 3000+ brands globally

SHIPPING

Order	Time
Domestic	M-F by 9:00 p.m. (EST)
Export	M-F by 6:00 p.m. (EST)

In-stock products normally ship the same day

NO MINIMUM ORDER FEES



YOU CAN FIND US AT...

f t y G+ in

NEW! FREE SHIPPING, FASTER DELIVERY, GLOBAL INVENTORY

Access our global inventory with free shipping on orders over \$150 USD & faster delivery

*Some exclusions apply, for more details see:
www.newark.com/help-delivery-information

